

Expandable braided sleeving in Polyethylene Terephthalate



PLIOSIL-PET




PET

Expansion ratio 1 to 2

Material: PET
Covering: ≥ 70%
Operating temperatures: -50 to +130°C
Melting point: +260°C
Flame resistance: self-extinguishing
V2 UL94
Specifications: EN 45545
halogene free

Applications: soft, flexible tubing for general use in the assembly of electrical wires in electrical cabinets and automation. Approved for rolling stock, this sheath is also used in the rail industry.



• Boxes

type		article number		cover according to DIN 65164	expansion in Ø (mm)	m
		black 010	grey 013			
PET	3	0624 0001 010	0624 0001 013	85%	2 ... 6	100
PET	4	0624 0002 010	0624 0002 013	89%	3 ... 8	100
PET	5	0624 0003 010	0624 0003 013	84%	4 ... 10	100
PET	6	0624 0004 010	0624 0004 013	81%	6 ... 12	100
PET	8	0624 0005 010	0624 0005 013	80%	8 ... 16	100
PET	10	0624 0006 010	0624 0006 013	78%	10 ... 20	100
PET	12	0624 0007 010	0624 0007 013	77%	12 ... 24	50
PET	15	0624 0008 010	0624 0008 013	76%	15 ... 27	50
PET	20	0624 0009 010	0624 0009 013	70%	19 ... 32	25
PET	25	0624 0010 010	0624 0010 013	74%	24 ... 38	25
PET	30	0624 0011 010	0624 0011 013	77%	28 ... 47	25
PET	40	0624 0013 010	0624 0013 013	74%	40 ... 63	25
PET	50	0624 0015 010	0624 0015 013	79%	45 ... 75	25
PET	60	0624 0016 010	0624 0016 013	83%	48 ... 92	25



• Industrial pack - on reel - long lengths

type		article number		cover according to DIN 65164	expansion in Ø (mm)	m
		black 010	grey 013			
PET	3 indus	0624 0201 010	0624 0201 013	85%	2 ... 6	1000
PET	4 indus	0624 0202 010	0624 0202 013	89%	3 ... 8	1000
PET	5 indus	0624 0203 010	0624 0203 013	84%	4 ... 10	400
PET	6 indus	0624 0204 010	0624 0204 013	81%	6 ... 12	400
PET	8 indus	0624 0205 010	0624 0205 013	80%	8 ... 16	300
PET	10 indus	0624 0206 010	0624 0206 013	78%	10 ... 20	300
PET	12 indus	0624 0207 010	0624 0207 013	77%	12 ... 24	300
PET	15 indus	0624 0208 010	0624 0208 013	76%	15 ... 27	300
PET	20 indus	0624 0209 010	0624 0209 013	70%	19 ... 32	200
PET	25 indus	0624 0210 010	0624 0210 013	74%	24 ... 38	200
PET	30 indus	0624 0211 010	0624 0211 013	77%	28 ... 47	150
PET	40 indus	0624 0213 010	0624 0213 013	74%	40 ... 63	100
PET	50 indus	0624 0215 010	0624 0215 013	79%	45 ... 75	100
PET	60 indus	0624 0216 010	0624 0216 013	83%	48 ... 92	50



Expandable braided sleeving in Polyethylene Terephthalate



PLIOSIL-PET
PLIOSIL-PET-S



• Dispenser box - short length (10 m)

type		article number		cover according to DIN 65164	expansion in Ø (mm)	 m
		black 010	grey 013			
PET	3 x 10 m	0624 0401 010	0624 0401 013	85%	2 ... 6	10
PET	4 x 10 m	0624 0402 010	0624 0402 013	89%	3 ... 8	10
PET	5 x 10 m	0624 0403 010	0624 0403 013	84%	4 ... 10	10
PET	6 x 10 m	0624 0404 010	0624 0404 013	81%	6 ... 12	10
PET	8 x 10 m	0624 0405 010	0624 0405 013	80%	8 ... 16	10
PET	10 x 10 m	0624 0406 010	0624 0406 013	78%	10 ... 20	10
PET	12 x 10 m	0624 0407 010	0624 0407 013	77%	12 ... 24	10
PET	15 x 10 m	0624 0408 010	0624 0408 013	76%	15 ... 27	10
PET	20 x 10 m	0624 0409 010	0624 0409 013	70%	19 ... 32	10
PET	25 x 10 m	0624 0410 010	0624 0410 013	74%	24 ... 38	10
PET	30 x 10 m	0624 0411 010	0624 0411 013	77%	28 ... 47	10
PET	40 x 10 m	0624 0413 010	0624 0413 013	74%	40 ... 63	10




PET-S

Expansion ratio 1 to 3

Material: PET
Covering: ≥ 55%
Operating temperatures: -50 to +130°C
Melting point: +260°C
Flame resistance: self-extinguishing
V2 UL94
Specifications: EN45545
halogene free

Applications: with its high expansion rate, this sleeve covers a wide range of uses (bulky connectors) or irregular shapes.



• Box

type		article number		cover according to DIN 65164	expansion in Ø (mm)	 m
		black 010	grey 013			
PET-S 15		0624 0018 010	0624 0018 013	78%	10 ... 30	25
PET-S 35		0624 0019 010	0624 0019 013	55%	20 ... 60	25



 A6/5-01

A6/5-02

C12/1-01 & A1/1-01

A4/4-03

Sleeves in lengths on
request



Expandable braided sleeving in POLYESTER V0




PLIOSIL-PET-V0



PET-V0

Material: PBT
Covering: ≥ 75%
Operating temperatures: -50 to +150°C
Melting point: +225°C
Flame resistance: self-extinguishing
 V0 UL94

Applications: this sleeve is designed to hold and protect cable harnesses in applications requiring high temperature resistance and when V0 quality is required.



• Boxes

type		article number		cover according to DIN 65164	expansion in Ø (mm)	m
		black 010	grey 013			
PET-V0	4	0624 0072 010	0624 0072 013	78%	3 ... 7	100
PET-V0	6	0624 0073 010	0624 0073 013	80%	5 ... 8	100
PET-V0	8	0624 0074 010	0624 0074 013	78%	7 ... 10	100
PET-V0	10	0624 0075 010	0624 0075 013	78%	9 ... 13	50
PET-V0	12	0624 0076 010	0624 0076 013	78%	11 ... 16	50
PET-V0	16	0624 0077 010	0624 0077 013	77%	15 ... 21	50
PET-V0	20	0624 0078 010	0624 0078 013	75%	20 ... 26	50
PET-V0	25	0624 0080 010	0624 0080 013	79%	24 ... 31	50
PET-V0	30	0624 0081 010	0624 0081 013	80%	28 ... 38	50
PET-V0	40	0624 0082 010	0624 0082 013	75%	38 ... 50	50



• Industrial pack - on reel - long length

type		article number		cover according to DIN 65164	expansion in Ø (mm)	m
		black 010	grey 013			
PET-V0	4	0624 0272 010	0624 0272 013	78%	3 ... 7	1000
PET-V0	6	0624 0273 010	0624 0273 013	80%	5 ... 8	400
PET-V0	8	0624 0274 010	0624 0274 013	78%	7 ... 10	300
PET-V0	10	0624 0275 010	0624 0275 013	78%	9 ... 13	300
PET-V0	12	0624 0276 010	0624 0276 013	78%	11 ... 16	300
PET-V0	16	0624 0277 010	0624 0277 013	77%	15 ... 21	300
PET-V0	20	0624 0278 010	0624 0278 013	75%	20 ... 26	200
PET-V0	25	0624 0280 010	0624 0280 013	79%	24 ... 31	200
PET-V0	30	0624 0281 010	0624 0281 013	80%	28 ... 38	150
PET-V0	40	0624 0282 010	0624 0282 013	75%	38 ... 50	100



A6/5-01



A6/5-02



C12/1-01 & A1/1-01



A4/4-03



Sleeves in lengths on
request

